

# Declaration of Performance

Certificate No. 0020-CPR-22v1  
CE

**1.**

Unique identification of the product type:

**CLIMCOVER Roll Alu2**  
**CLIMCOVER Roll Alu2 Strong**  
**CLIMCOVER Slab Alu2**  
**CLIMCOVER Slab Alu2 Standard**

**2.**

Type, batch or serial number or any element allowing identification of the construction product as required under Article 11(4) of the CPR:

**See product label**

**3.**

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Thermal Insulation for Building Equipment and Industrial Installations (ThIBEII)**

**4.**

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Saint-Gobain Isover UK Limited, Whitehouse Industrial Estate, Runcorn, Cheshire, WA7 3DP, UK**

**5.**

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

**6.**

System or systems of Assessment and Verification of Constancy of Performance (AVCP) of the construction product as set out in Annex V:

**System 1 (Reaction to fire)**  
**System 3**

**7.**

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified certification body Element Materials Technology Rotterdam B.V. No. 2812 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (2812-CPR-BA0158) for Reaction to fire.**

## 8. Declared performance

Harmonised Technical Standard: EN 14303:2009 + A1:2013

Essential characteristics	Performance	Unit	Declared performance		
<b>Product name</b>			CLIMCOVER Roll Alu2		
<b>Product thickness</b>		mm	25	40	50
<b>Reaction to fire</b>		Euroclass	A2-s1, d0		
<b>Acoustic absorption index</b>	Sound absorption		NPD		
<b>Thermal resistance</b>	Thermal conductivity [in W/(m.K)]				
	at 10°C		0.032	0.032	0.032
	at 40°C		0.037	0.037	0.037
	at 50°C		0.039	0.039	0.039
	at 100°C		0.049	0.049	0.049
	at 120°C		0.054	0.054	0.054
	Dimensions	mm	25	40	50
	Tolerances		T3	T3	T3
<b>Water permeability</b>	Water absorption		NPD		
<b>Water vapour permeability</b>	Water vapour diffusion resistance		NPD		
<b>Compressive strength</b>	Compressive stress or compressive strength for flat products		NPD		
<b>Rate of release of corrosive substances</b>	Trace quantity of ions Cl		NPD		
	Trace quantity of ions F		NPD		
	Trace quantity of ions SiO <sub>3</sub>		NPD		
	Trace quantity of ions Na		NPD		
	Value of pH		NPD		
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances		(d)		
<b>Continuous glowing combustion</b>	Continuous glowing combustion		(d)		
<b>Durability of Reaction to fire against ageing/degradation</b>	Durability characteristics		(a)		
<b>Durability of thermal resistance against ageing/degradation</b>	Thermal conductivity		See above (b)		
	Dimensional stability, or Maximum service temperature		Maximum service temperature (e)		
<b>Durability of thermal resistance against high temperature</b>	Thermal conductivity		See above		
	Maximum service temperature		(e)		
<b>Durability of Reaction to fire against high temperature</b>	Durability characteristics		(c)		

**NPD** No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time.  
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) The fire performance of mineral wool products does not deteriorate with high temperature.  
The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.
- (d) European Test Methods are under development - the standard will be amended when available.
- (e) The maximum service temperature testing needs not to be done as declared thermal conductivity is given for temperatures  $\leq 150^{\circ}\text{C}$  and the binder cures at  $T > 200^{\circ}\text{C}$ .

### Declaration of Performance

Document No. 0020-CPR-22v1  
19 - 05 - 2022

## 8. Declared performance

Harmonised Technical Standard: EN 14303:2009 + A1:2013

Essential characteristics	Performance	Unit	Declared performance		
<b>Product name</b>	CLIMCOVER Roll Alu2 Strong				
<b>Product thickness</b>		mm	25	40	50
<b>Reaction to fire</b>		Euroclass	A2-s1, d0		
<b>Acoustic absorption index</b>	Sound absorption		NPD		
<b>Thermal resistance</b>	Thermal conductivity [in W/(m.K)]				
	at 10°C		0.032	0.032	0.032
	at 40°C		0.036	0.036	0.036
	at 50°C		0.038	0.038	0.038
	at 100°C		0.045	0.045	0.045
	at 120°C		0.049	0.049	0.049
	Dimensions	mm	25	40	50
	Tolerances		T3	T3	T3
<b>Water permeability</b>	Water absorption		NPD		
<b>Water vapour permeability</b>	Water vapour diffusion resistance		NPD		
<b>Compressive strength</b>	Compressive stress or compressive strength for flat products		NPD		
<b>Rate of release of corrosive substances</b>	Trace quantity of ions Cl		NPD		
	Trace quantity of ions F		NPD		
	Trace quantity of ions SiO <sub>3</sub>		NPD		
	Trace quantity of ions Na		NPD		
	Value of pH		NPD		
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances		(d)		
<b>Continuous glowing combustion</b>	Continuous glowing combustion		(d)		
<b>Durability of Reaction to fire against ageing/degradation</b>	Durability characteristics		(a)		
<b>Durability of thermal resistance against ageing/degradation</b>	Thermal conductivity		See above (b)		
	Dimensional stability, or Maximum service temperature		Maximum service temperature (e)		
<b>Durability of thermal resistance against high temperature</b>	Thermal conductivity		See above		
	Maximum service temperature		(e)		
<b>Durability of Reaction to fire against high temperature</b>	Durability characteristics		(c)		

**NPD** No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time.  
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) The fire performance of mineral wool products does not deteriorate with high temperature.  
The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.
- (d) European Test Methods are under development - the standard will be amended when available.
- (e) The maximum service temperature testing needs not to be done as declared thermal conductivity is given for temperatures ≤150°C and the binder cures at T >200°C.

### Declaration of Performance

Document No. 0020-CPR-22v1  
19 - 05 - 2022

## 8. Declared performance

Harmonised Technical Standard: EN 14303:2009 + A1:2013

Essential characteristics	Performance	Unit	Declared performance	
<b>Product name</b>			CLIMCOVER SLAB Alu2	
<b>Product thickness</b>		mm	40	50
<b>Reaction to fire</b>		Euroclass	A2-s1, d0	
<b>Acoustic absorption index</b>	Sound absorption		NPD	
<b>Thermal resistance</b>	Thermal conductivity [in W/(m.K)]			
	at 10°C		0.032	0.032
	at 40°C		0.036	0.036
	at 50°C		0.038	0.038
	at 100°C		0.045	0.045
	at 120°C		0.049	0.049
	Dimensions	mm	40	50
	Tolerances		T3	T3
<b>Water permeability</b>	Water absorption		NPD	
<b>Water vapour permeability</b>	Water vapour diffusion resistance		NPD	
<b>Compressive strength</b>	Compressive stress or compressive strength for flat products		NPD	
<b>Rate of release of corrosive substances</b>	Trace quantity of ions Cl		NPD	
	Trace quantity of ions F		NPD	
	Trace quantity of ions SiO <sub>3</sub>		NPD	
	Trace quantity of ions Na		NPD	
	Value of pH		NPD	
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances		(d)	
<b>Continuous glowing combustion</b>	Continuous glowing combustion		(d)	
<b>Durability of Reaction to fire against ageing/degradation</b>	Durability characteristics		(a)	
<b>Durability of thermal resistance against ageing/degradation</b>	Thermal conductivity		See above (b)	
	Dimensional stability, or Maximum service temperature		Maximum service temperature (e)	
<b>Durability of thermal resistance against high temperature</b>	Thermal conductivity		See above	
	Maximum service temperature		(e)	
<b>Durability of Reaction to fire against high temperature</b>	Durability characteristics		(c)	

**NPD** No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time.  
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) The fire performance of mineral wool products does not deteriorate with high temperature.  
The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.
- (d) European Test Methods are under development - the standard will be amended when available.
- (e) The maximum service temperature testing needs not to be done as declared thermal conductivity is given for temperatures  $\leq 150^{\circ}\text{C}$  and the binder cures at  $T > 200^{\circ}\text{C}$ .

### Declaration of Performance

Document No. 0020-CPR-22v1  
19 - 05 - 2022

## 8. Declared performance

Harmonised Technical Standard: EN 14303:2009 + A1:2013

Essential characteristics	Performance	Unit	Declared performance	
<b>Product name</b>			CLIMCOVER SLAB Alu2 STANDARD	
<b>Product thickness</b>		mm	40	50
<b>Reaction to fire</b>		Euroclass	A2-s1, d0	
<b>Acoustic absorption index</b>	Sound absorption		NPD	
<b>Thermal resistance</b>	Thermal conductivity [in W/(m.K)]			
	at 10°C		0.032	0.032
	at 40°C		0.036	0.036
	at 50°C		0.038	0.038
	at 100°C		0.045	0.045
	at 120°C		0.049	0.049
	Dimensions	mm	40	50
	Tolerances		T3	T3
<b>Water permeability</b>	Water absorption		NPD	
<b>Water vapour permeability</b>	Water vapour diffusion resistance		NPD	
<b>Compressive strength</b>	Compressive stress or compressive strength for flat products		NPD	
<b>Rate of release of corrosive substances</b>	Trace quantity of ions Cl		NPD	
	Trace quantity of ions F		NPD	
	Trace quantity of ions SiO <sub>3</sub>		NPD	
	Trace quantity of ions Na		NPD	
	Value of pH		NPD	
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances		(d)	
<b>Continuous glowing combustion</b>	Continuous glowing combustion		(d)	
<b>Durability of Reaction to fire against ageing/degradation</b>	Durability characteristics		(a)	
<b>Durability of thermal resistance against ageing/degradation</b>	Thermal conductivity		See above (b)	
	Dimensional stability, or Maximum service temperature		Maximum service temperature (e)	
<b>Durability of thermal resistance against high temperature</b>	Thermal conductivity		See above	
	Maximum service temperature		(e)	
<b>Durability of Reaction to fire against high temperature</b>	Durability characteristics		(c)	

**NPD** No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time.  
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) The fire performance of mineral wool products does not deteriorate with high temperature.  
The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.
- (d) European Test Methods are under development - the standard will be amended when available.
- (e) The maximum service temperature testing needs not to be done as declared thermal conductivity is given for temperatures ≤150°C and the binder cures at T >200°C.

### Declaration of Performance


Document No. 0020-CPR-22v1  
19 - 05 - 2022

**9.**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Dean O'Sullivan". The signature is fluid and cursive, written on a light grey background.

**Dean O'Sullivan**, Managing Director

Runcorn.

19th May 2022



**Isover**

Whitehouse Industrial Estate,  
Runcorn WA7 3DP

**Customer Service -  
Order Placement and Enquiries**

Tel: 01473 820820  
Email: [iukcustomerservice@saint-gobain.com](mailto:iukcustomerservice@saint-gobain.com)

**Technical Support Centre**

Tel: 01473 820850  
Email: [technicalsupport@saint-gobain.com](mailto:technicalsupport@saint-gobain.com)

**[insulation-uk.com](http://insulation-uk.com)**

Published date: May 2022  
Certificate No.: 0020-CPR-22v1

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [insulation-uk.com](http://insulation-uk.com)

Isover: Whitehouse Industrial Estate, Runcorn, Cheshire, WA7 3DP. Tel +44 (0) 1473 822093.  
Saint-Gobain Isover UK Limited, Registered in England. Company Number 10442670.  
Registered Office: Saint-Gobain House, East Leake, Loughborough, Leicestershire LE12 6JU.