



# TIMBER FRAME BATT 43

## Thermal Insulation for Timber Frame Walls

Timber Frame Batt 43 is a glass mineral wool batt providing thermal performance in timber frame walls. Supplied in a range of thicknesses, the strong, resilient and flexible batts are 570mm wide to fit between standard timber studs.



## Features and Benefits



### Thermal performance

Thermal conductivity of 0.043 W/m.K.  
Helps to reduce heat loss within the building envelope and decrease energy costs.



### Non-combustible

Achieves a Euroclass A1 Reaction to Fire classification, according to BS EN 13501-1.



### Recycled glass

Manufactured from up to 75% recycled glass.



### Quick and easy to install

570mm widths push fit between 600mm timber stud centres with no need for additional fixings.

## Product Specification

Product code	Thickness (mm)	Width (mm)	Length (mm)	Batts per pack	Pack area (m <sup>2</sup> )	Packs per pallet	Pallet area (m <sup>2</sup> )	λ <sub>D</sub> Declared thermal conductivity (W/m.K)	R <sub>D</sub> Declared thermal resistance (m <sup>2</sup> .K/W)
5200625339	90	570	1175	12	8.04	24	192.89	0.043	2.05
5200625337	140	570	1175	8	5.36	24	128.59	0.043	3.25



# CHARACTERISTICS

Characteristic	Description
<b>Thermal</b>	Timber Frame Batt 43 has a declared thermal conductivity of 0.043 W/m.K under BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
<b>Fire</b>	Euroclass A1 Reaction to Fire classification according to BS EN 13501-1.
<b>Environmental</b>	All ISOVER products are manufactured under Environmental Management System - ISO 14001. Zero Ozone Depletion Potential (ODP) and Global Warming Potential (GWP) < 5. The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases. BES 6001 Rating "Good" - The Framework Standard for Responsible Sourcing.
<b>BRE statements</b>	Timber Frame Batt 43 corresponds to the BRE Global Green Guide online generic specification glass wool insulation ref 815320005, which achieves a summary rating of A+ within the Domestic, Health, Industrial, Commercial, Retail and Education categories.
<b>Quality</b>	All ISOVER products are manufactured under Quality Management Standard - ISO 9001. Timber Frame Batt 43 is manufactured in accordance with BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
<b>Building regulations</b>	Helps to meet the requirements of UK thermal building regulations.
<b>Recycled content</b>	Timber Frame Batt 43 is manufactured from up to 75% recycled glass.
<b>Durability</b>	Thermal conductivity of mineral wool products does not change with time. Experience has shown the fibre structure to be stable and the fibre matrix contains no other gases than atmospheric air (see standard EN 13162). Will not sustain vermin, nor breed or promote fungi or bacteria.
<b>Handling and storage</b>	Information regarding storage, installation and handling of ISOVER products, or health & safety information, can be found here.
<b>Health and safety</b>	
<b>Certification</b>	CE marked (1121-CPR-BA0053) to BS EN 13162. Designation codes: MW-EN 13162-T3.

## Customer Service Centre - Order Placement and Enquiries

**Tel:** 01473 820820

**Email:** iukcustomerservice@saint-gobain.com

## ISOVER Address:

Whitehouse Industrial Estate,  
Runcorn, Cheshire, WA7 3DP

## Technical Enquiries - Advice and Support Line

**Tel:** 01473 820850

**Email:** technicalsupport@saint-gobain.com

**Insulation-UK.com**