



TIMBER FRAME ROLL 35



Thermal Insulation for Timber Frame Walls

Timber Frame Roll 35 is a glass mineral wool roll providing thermal performance and acoustic benefits in timber frame walls. The strong, resilient and flexible rolls are pre-cut to 2 x 570mm (to fit between standard 600mm stud centres) or 3 x 400mm widths.

Features and Benefits



Thermal

Thermal performance

Thermal conductivity of 0.035 W/m.K.
Helps to reduce heat loss within the building envelope and decrease energy costs.



Non-combustible

Non-combustible

Achieves a Euroclass A1 Reaction to Fire classification, according to BS EN 13501-1.



Acoustic

Acoustic benefits

Reduces unwanted noise from external sources helping to improve the acoustic comfort of those living within the building.



Easy to install

Quick and easy to install

Push fits between timber stud centres with no need for additional fixings.



Recycled glass

Recycled glass

Manufactured from up to 75% recycled glass.

Product Specification

Product code	Thickness (mm)	Width (mm)	Length (mm)	Pack area (m ²)	Packs per pallet	Pallet area (m ²)	λ ₀ Declared thermal conductivity (W/m.K)	R ₀ Declared thermal resistance (m ² .K/W)
5200625573	90	2 x 570	5300	6.04	18	108.76	0.035	2.55
52006819811	100	2 x 570	5000	5.70	18	102.60	0.035	2.85
5200625583	140	2 x 570	4000	4.56	18	82.08	0.035	4.00
5200822660	140	3 x 400	4000	4.80	18	86.40	0.035	4.00



CHARACTERISTICS

Characteristic	Description
Thermal	Timber Frame Roll 35 has a declared thermal conductivity of 0.035 W/m.K under BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
Fire	Euroclass A1 Reaction to Fire classification according to BS EN 13501-1.
Environmental	All ISOVER products are manufactured under Environmental Management System - ISO 14001. Zero Ozone Depletion Potential (ODP) and Global Warming Potential (GWP) < 5. The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases. BES 6001 Rating "Good" - The Framework Standard for Responsible Sourcing.
BRE statements	Timber Frame Roll 35 corresponds to the BRE Global Green Guide online generic specification glass wool insulation ref 815320003, which achieves a summary rating of A+ within the Domestic, Health, Industrial, Commercial, Retail and Education categories.
Quality	All ISOVER products are manufactured under Quality Management Standard - ISO 9001. Timber Frame Roll 35 is manufactured in accordance with BS EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
Building regulations	Helps to meet the requirements of UK thermal building regulations.
Recycled content	Timber Frame Roll 35 is manufactured from up to 75% recycled glass.
Durability	Thermal conductivity of mineral wool products does not change with time. Experience has shown the fibre structure to be stable and the fibre matrix contains no other gases than atmospheric air (see standard EN 13162). Will not sustain vermin, nor breed or promote fungi or bacteria.
Handling and storage	Information regarding storage, installation and handling of ISOVER products, or health & safety information, can be found here.
Health and safety	
Certification	CE marked (1121-CPR-BA0053) to BS EN 13162. Designation code: MW-EN 13162-T1.

**Customer Service Centre -
Order Placement and Enquiries****Tel:** 01473 820820**Email:** iukcustomerservice@saint-gobain.com**ISOVER Address:**Whitehouse Industrial Estate,
Runcorn, Cheshire, WA7 3DP**Technical Enquiries -
Advice and Support Line****Tel:** 01473 820850**Email:** technicalsupport@saint-gobain.com**Insulation-UK.com**